

Commercial Rubber

70° Shore Commercial Rubber is a natural rubber and Styrene Butadiene rubber blend. It is used where a cheaper quality material will suit.

In simple applications such as picking pieces, dust seals, protection pads etc. where the material is not coming under duress.

Properties	Values
Colour	: Black
Compound	: NR/SBR
Density (Specific Gravity)	: 1.60
Hardness (Degrees Shore A)	: 70° +/- 5
Tensile Strength (kg/cm ²)	: 30
Elongation at Break	: 200%
Temperature Range	: -20 to +70°C
Abrasion Resistance	: NA

This product is available for bespoke manufacturing.



Gaskets



Strips



Cut Parts

Thickness	:	0.5mm to 50mm
Sheet Size	:	1.4m wide x 10m long (1mm to 6mm) 1.4m wide x 5m long (8mm to 25mm) 1m wide x 2m long (25mm, 30mm, 40mm & 50mm)
Finish	:	Smooth Finish (SS) & Cloth Finish (CC)
Cutting	:	Standard press-tools

The information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check and test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.