

5 Bar Checker Plate Rubber Matting

A general purpose matting with a 5 Bar Checker Plate Pattern, suitable as a floor covering temporary or semi-permanent use in industrial & commercial areas. Can also be used to line shelves or drawers in garage or workshop environments.



Colour : Black
Surface : Checkerplate (5 bar)
Width : 1200mm
Polymer : SBR / NR Blend

Specifications	Values	Test Methods
Compression Set (22 Hours @ 70°C)	30% Maximum	ASTM D395 Method B
Elongation at Break	250% Minimum	ASTM D412
Highest Recommended Working Temperature	70°C Maximum	None
Intermittent Working Temperature	90°C Short Bursts Only	None
Lowest Recommended Working Temperature	-20°C Minimum	None
Shore Hardness (Shore A)	65° Shore +/- 0.05	ASTM D2240
Specific Gravity	1.55 g/cm +/- 0.05	ASTM D2240
Tensile Strength	3 MPA Minimum	ASTM D412

The information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check and test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.