

HabasitLINK®

M5060 Flat Top 2"





Description

- 0% open area
- Solid plate
- Imperial belt width
- Dynamic open hinge, easy to clean
- Strong link design (1" link-pitch)
- Rod diameter 7 mm (0.27")
- Smart Fit rod retention
- Food approved materials available

Available accessories

- Flights



Belt data

Belt material		PP		PE	
Rod material		PP	PA	PE	PA
Nominal tensile strength F'_N straight run	N/m	18000	22000	8000	10000
	lb/ft	1233	1507	548	685
Temperature range	°C	5 - 105	5 - 105	-70 - 65	-46 - 65
	°F	40 - 220	40 - 220	-94 - 150	-50 - 150
Belt weight m_B	kg/m ²	8.8	8.8	9.1	9.1
	lb/sqft	1.8	1.8	1.86	1.86

Belt material		POM		POM +IM	
Rod material		PE	PA	PE	PA
Nominal tensile strength F'_N straight run	N/m	14000	30000	14000	30000
	lb/ft	959	2055	959	2055
Temperature range	°C	-40 - 65	-40 - 93	-40 - 65	-40 - 93
	°F	-40 - 150	-40 - 200	-40 - 150	-40 - 200
Belt weight m_B	kg/m ²	13.1	13.1	13.1	13.1
	lb/sqft	2.68	2.68	2.68	2.68

Diameter of idling rollers (minimum)		Diameter of support rollers (minimum)		Diameter for gravity take-up and center drive rollers (minimum)		Backbending radius for elevators without sideguards or hold down devices (minimum)		Backbending radius for elevators with sideguards or hold down devices (minimum)	
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
90	3.5	100	4	150	6	150	6	250	10

Use the largest possible backbending radius for elevators with side guards or hold down devices.

Standard range of belt widths b_0

mm (nom.)	101	152	203	254	304	356	406	457	508	559	609	660	711	etc.
inch (nom.)	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.0	22.0	24.0	26.0	28.0	etc.

Real belt widths are in most cases 0.1% to 0.3% smaller.

Standard belt widths in increments 4.0" (101 mm). Non-standard widths are offered in increments of 1.0" (25.4 mm) Smallest possible width 4.0" (101 mm).

HabasitLINK®

M5060 Flat Top 2"



For detailed material properties refer to the HabasitLINK® Engineering Guidelines or contact your Habasit representative.

The nominal tensile strength is valid for 23 °C (73 °F). The admissible tensile force depends on the operating temperature near the drive sprockets. Within the temperature range allowed, the admissible tensile force may vary from 100% to 20% of the nominal tensile strength. For detailed information and correct calculation of effective tensile force refer to the Calculation Guide in the HabasitLINK® Engineering Guidelines.

Product liability, application considerations

If the proper selection and application of Habasit products are not recommended by an authorized Habasit sales specialist, the selection and application of Habasit products, including the related area of product safety, are the responsibility of the customer.

All indications / information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. The data provided herein are based on laboratory work with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experiences can lead to modifications and changes within a short time without prior notice.

BECAUSE CONDITIONS OF USE ARE OUTSIDE OF HABASIT'S AND ITS AFFILIATED COMPANIES CONTROL, WE CANNOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS MENTIONED HEREIN. THIS ALSO APPLIES TO PROCESS RESULTS / OUTPUT / MANUFACTURING GOODS AS WELL AS TO POSSIBLE DEFECTS, DAMAGES, CONSEQUENTIAL DAMAGES, AND FURTHER-REACHING CONSEQUENCES.